

Specification

Filtration · Rapid Tests · Water Analysis · Chromatography · Bioanalysis Filtration · Schnellteste · Wasseranalytik · Chromatographie · Bioanalytik

Product: CHROMAFIL® Cellulose Mixed Esters (MV)

REF: 729004

Filters are HPLC certified for low level UV-absorbing

substances for gaining accurate chromatographic results

Housing material: Polypropylene (PP)

Colour code: top: colourless

bottom: yellow

Membrane filter material: Cellulose Mixed Esters

Pore diameter: 0.45 µm

Filter diameter: 25 mm

Filtration area: $\sim 4.9 \text{ cm}^2$

Pressure stability: > 12 bar

Connections inlet: Female luer lock

Connections outlet: Male luer

Dead volume: $\sim 80 \mu L$

HPLC-test

Conditions: Two mL of the solvent (specified under the chromatogram)

were applied to the filter; 100 µL of the filtrate were injected

to the HPLC.

Eluent A: water

Eluent B: acetonitrile

Gradient: $10\% \rightarrow 95\%$ B in 25 minutes

Flow rate: 0.5 mL/min

Sensitivity: -5 to 10 mAU at 254 nm

Column: 125/4 NUCLEODUR[™] C18 Gravity 5 µm (REF: 760100.40)



Specification

 $\label{eq:Filtration} Filtration \cdot Rapid Tests \cdot Water Analysis \cdot Chromatography \cdot Bioanalysis \\ Filtration \cdot Schnellteste \cdot Wasseranalytik \cdot Chromatographie \cdot Bioanalytik \\$

