

## **Specification**

Filtration · Rapid Tests · Water Analysis · Chromatography · Bioanalysis Filtration · Schnellteste · Wasseranalytik · Chromatographie · Bioanalytik

Product: CHROMAFIL® Glass Fibre (GF)

REF: 729028

Filters are HPLC certified for low level UV-absorbing

substances for gaining accurate chromatographic results

Housing material: Polypropylene (PP)

Colour code: top: yellow

bottom: black

Membrane filter material: Glass Fibre

Pore diameter: 1.0 µm (nominal)

Filter diameter: 25 mm

Filtration area:  $\sim 4.9 \text{ cm}^2$ 

Pressure stability: > 12 bar

Connections inlet: Female luer lock

Connections outlet: Male luer

Dead volume: ~ 80 µL

## **HPLC-test**

Conditions: Two mL of the solvent (specified under the chromatograms)

were applied to the filter; 100 µL of the filtrate were injected

to the HPLC.

Eluent A: water

Eluent B: acetonitrile

Gradient:  $10\% \rightarrow 95\%$  B in 25 minutes

Flow rate: 0.5 mL/min


Sensitivity: -5 to 10 mAU at 254 nm

Column: 125/4 NUCLEODUR® C18 Gravity 5 µm (REF: 760100.40)




## **Specification**


 $\label{eq:Filtration} Filtration \cdot Rapid Tests \cdot Water Analysis \cdot Chromatography \cdot Bioanalysis \\ Filtration \cdot Schnellteste \cdot Wasseranalytik \cdot Chromatographie \cdot Bioanalytik \\$ 



## Methanol filtrate



Water filtrate



5955 Peachtree Corners E | Suite A | Norcross, GA 30071 USA | 1.800.SORBTECH | +1.770.936.0323